

VA 804 FB

**CARRIAGE FOR 420 MM RESTRAINT LENGTH
WITH CONVEYOR BELT**



VA 804 FB with long
conveyor belt 1300 mm



A Bluetooth interface facilitates
fast, competent programming,
taken care of by the GRAEF
parent plant.

VA 804 FB with conveyor belt

BENEFITS

- Conveyor belt in stainless steel chain belt design, non-rusting
- Conveyor belt length optionally between 690 and 1300 mm
- Fast, simple installation and removal of the conveyor belt
- Integrated stacking correction for straight stacks
- Conveyor belt width 250 mm
- PLU program included

CARRIAGE

- Carriage can be folded for cleaning
- Automatic, smooth running carriage
- Self regulating carriage advance number 30 - 60 strokes/min.
- Motorised slicing product feed
- Slicing product advance in a mount 420 mm
- Simple and rapid slicing product fixation through patented food holder "Fork" and highslicing product retaining bar

OPTION

- Machine table (Mati 1) made of stainless steel (L x W x H) 656 x 553 x max. 720 mm
- Machine table (Mati 2) made of stainless steel, on rollers (L x W x H) 656 x 520 x max. 776 mm
- Machine table (Mati 3) made of stainless steel, on rollers and large delivery (L x W x H) 850 x 553 x max. 816 mm



Mati 1



Mati 2



Mati 3

Recommended for
conveyor belt 1300 mm



TECHNICAL DATA

	Product no.	VA 804 FB
	Motor power	500 watts 230 V~ alternating or 400 V~ three-phase current
	Blade (Ø mm)	Ø 300 mm, smooth, solid steel blade
	Blade speed	229/rpm
	Slices per minute max.	60/rpm
	Slice thickness min. - max. (mm)	0.5 – 10 mm
	Stack height	60 mm
	Slicing speed	30 - 60 strokes / min.
	Emission noise level	< 69 dBA
	Slice size (L x H mm)	180 x 250 mm
	Interface	serial
	Placement facilities	Stacking, longitudinal and traverse bays, Round placement (depending on the model)
	Restraint length (mm)	230 mm
	Slicing product size with transport chain (mm)	max: 240 x 180 mm / min. 30 x 30 mm
	Conveyor belt (L x W mm)	690 x 250 mm (short) / 1300 x 250 mm (long)
	Footprint (L x W mm)	540 x 440 mm
	Exterior dimensions (L x W x H)	600 x 1060 x 500 mm
	Workspace (L x W x H)	700 x 1100 x 1400 mm
	Net / gross weight	70 kg / 100 kg
	Operating period	Continuous duty
	Warranty	1 year