

## VA 804 FB Interleaver

CARRIAGE FOR 420 MM RESTRAINT LENGTH  
WITH CONVEYOR BELT AND INTERLEAVER



A Bluetooth interface facilitates fast, competent programming, taken care of by the GRAEF parent plant.

### VA 804 FB Interleaver - with conveyor belt and interleaver

The interleaver facilitates automatic insertion of leaves or foils between the discharged sliced product. Furthermore, trays can be inserted as backings. The unit has automatic stacking correction for the stacking function. An integrated control terminal facilitates individual customisation to the slicing machine program. With the separation appliance, it is possible to insert up to two foils, leaves or trays simultaneously. Possible placement programs are stacking and fanning.

### BENEFITS

#### CARRIAGE

- Carriage can be folded for cleaning
- Automatic, smooth running carriage
- Self regulating carriage advance number 30 - 60 strokes/min.
- Motorised slicing product feed
- Slicing product advance in a mount 420 mm
- Simple and rapid slicing product fixation through patented food holder "Fork" and highslicing product retaining bar

#### INTERLEAVER

- For automatic insertion of leaves, foils or trays
- Model 205 E for tray mode
- Model 205 ES for tray and stacking mode

#### ACCESSORIES

- Separator appliance to separate from 2 pack foils or trays
- Three-segment filter (pressure control device with manometer, moisture separator, oil and dirt filter)



### TECHNICAL DATA

| Product no.                          | INTERLEAVER                               |
|--------------------------------------|---|
| Dimensions (L x W x H)               | 540 x 270 x 550 mm                        |
| Voltage / Frequency                  | 230 V / 50 Hz                             |
| Special voltage                      | Available on request (e.g. 110 V / 60 Hz) |
| Placement speed, trays, paper, foils | max: 60/rpm                               |
| Operating pressure                   | 4 - 5 bar                                 |
| Dimensions, trays, paper, foils      | max. 170 x 250 mm                         |
| Weight paper, foils                  | min. 65 g/m <sup>2</sup>                  |
| Warranty                             | 1 year                                    |